

# TSH 金屬臥式離心式泵浦

<b>TSH</b> (1) <b>TYPE</b> 機型編號 TSH : Direct drive with flange mounted motor TSHC : Coupling drive with IEC B3 foot mounted motor	<b>50</b> (2) <b>In-Outlet</b> 進出口徑	<b>2</b> (3) <b>HP</b> 馬力 0=0.5HP 1=1HP 2=2HP 3=3HP 5=5HP 7.5=7.5HP 10=10HP 15=15HP 20=20HP	<b>C</b> (4) <b>Fixed Seal</b> 軸封固定環 C=Ceramic S=Silicon carbide T=Tungsten carbide	<b>C</b> (5) <b>Rotational Seal</b> 軸封轉動環 C=Carbon S=Silicon carbide T=Tungsten carbide	<b>4</b> (6) <b>Wet-end material</b> 泵浦材質 4=SUS304(SCS13) 6=SUS316(SCS14) C=Cast iron (FC20)	<b>V</b> (7) <b>O-RING</b> O環 V=FKM (VITON) N=NBR T=PTFE	<b>6</b> (8) <b>Frequency</b> 週波數 5=50HZ 6=60HZ
--	--	---	---	---	--	---	--



## ■ 特性：

1. 泵浦本體及葉輪採用精密脫蠟鑄造，表面平順流道光滑且無砂孔現象。
2. 泵體材質有SUS304、SUS316及FC20，採特殊合金Titanium & C-276可接受客製化訂單，軸封材質有C(陶磁)、S(磁化矽)及T(碳化鎢)，可依上列材質的耐侵蝕性選用。

## ■ Specifications

Model 規格	Curve 曲線		HP 馬力	Connection 口徑 Female threaded ports 內牙法蘭	Max.Flow全流量 (L/min)		Max.Head全揚程 (M)	
	50HZ	60HZ			50HZ	60HZ	50HZ	60HZ
TSH-25-0	a	A	0.5	1"	110	110	12.5	15
TSH-25-1	b	B	1	1"	180	150	12.5	20
TSH-40-1	c	C	1	1.5"	300	280	12.5	15
TSH-50-2	d	D	2	2"	350	310	17.5	20
TSH-50-3	e	E	3	2"	450	350	21	25
TSH-65-3	f	F	3	2.5"	600	580	15	20
TSH-50-5	g	G	5	2"	450	350	33	40
TSH-80-5	h	H	5	3"	700	800	23	30
TSH-50-7.5	i	I	7.5	2"	400	410	50	60
TSH-80-7.5	j	J	7.5	3"	700	880	30	35
TSH-100-7.5	k	K	7.5	4"	1400	1400	20	20
TSH-50-10	l	L	10	2"	460	550	60	75
TSH-80-10	m	M	10	3"	800	980	40	45
TSH-100-10	n	N	10	4"	1600	1650	20	20
TSH-125-10	o	O	10	5"	1600	1600	15	15
TSH-80-15	p	P	15	3"	900	1100	45	60
TSH-100-15	q	Q	15	4"	1300	1656	30	30
TSH-125-15	r	R	15	5"	2000	2050	20	20
TSH-100-20	s	S	20	4"	1500	1800	40	40
TSH-125-20	t	T	20	5"	2000	2200	30	30

